



DIMENSIONAL VARIABLES

DRAWING NOT TO SCALE; DIMENSIONS IN INCHES

DOOR NO.	A	B	C	H
MILLIMETERS				

ACTUAL DOOR SIZE IS PRODUCED IN MILLIMETERS
REQUESTED DOOR SIZE IS CONVERTED TO MILLIMETERS
AND ROUNDED UP TO THE NEAREST 10MM

ELECTRICAL OPTIONS

- ☐ 460v - 3ph
☐ 230v/208v - 3ph
☐ 230v/208v - 1ph
☐ 575v - 3ph
☐ OTHER

STANDARD FEATURES

- ONE THRU-BEAM PHOTOEYE SET MOUNTED IN SIDE COLUMN AT 16" FROM FLOOR-FACTORY INSTALLED.
- ONE THRU-BEAM PHOTOEYE SET-FIELD INSTALLED.
- VARIABLE DOOR OPENING SPEED; UP TO 118"/SEC
- DOOR CLOSING SPEED OF 30"/SECOND
- PROGRAMMABLE UPPER AND LOWER LIMITS
- SYSTEM 4 CONTROL BOX (8 1/2"x16 1/2")
- BRAKE RELEASE LEVER ON SIDE COLUMN
- ELECTRICAL FAIL SAFE REVERSING EDGE.

STANDARD OPTIONS

- ☐ TOP DUST COVER
☐ SLANT HOOD
☐ FRONT AND BOTTOM HEAD COVERS
☐ RIGHT HAND DRIVE
☐ REMOTE MOUNTED EGRESS LEVER

ACTIVATION

- ☐ — PRESENSE SENSOR
☐ — PULLCORDS
☐ — RADIO CONTROL w/2 X-MITTERS
☐ — MOTION DETECTOR
☐ — PUSHBUTTON
☐ — FLOOR LOOP CONTROLLER
☐ — OTHERS (DESCRIBE IN NOTES)

OPTION NOTES

ADDITIONAL NOTES:

RYTEC CORPORATION

ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING

SPIRAL FV Model STT-L SYSTEM 4
FOR DOOR WIDTH UP TO 13'-1", HEIGHT UP TO 12'-9"

CUSTOMER:

LOCATION:

DATE:
12/2/11

DRAWING NO.: 401074-19T

TEMPLATE:
981655temp.dwg
REV.: —

APPROVAL SIGNATURE

FABRICATION CAN PROCEED ACCORDING TO THE
 SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY:

PRINT NAME: _____

SIGNATURE: _____

DATE: _____

REV	DESCRIPTION	DATE	BY