



DRAWING NOT TO SCALE, ALL DIMENSIONS IN INCHES

DOOR NO.	A	B	C	D	E	H

MODEL TS6000-INS

ELECTRICAL OPTIONS

- ☐ 460v - 3ph
- ☐ 230v/208v - 3ph
- ☐ 575v - 3ph
- ☐ OTHER

STANDARD FEATURES

1. INSULATED 1" THICK BLUE FOAM PANEL WITH RILON INNER CORE
2. FIBERGLASS THERMAL BREAKS AROUND DOOR PERIMETER
3. QUAD SEALING SIDE COLUMNS, DUAL HEAD SEALS
4. WIRELESS (NO COIL CORD) THERMALLY ISOLATED COMPOSITE BOTTOM BAR WITH DUAL AIR REVERSING EDGE
5. SYSTEM 4 AC DRIVE
6. LEFT HAND MOTOR MOUNT
7. SELF REPAIRING/RESETTING DOOR - IF BOTTOM BAR IS IMPACTED FROM EITHER DIRECTION, THE DOOR RECOGNIZES AND AUTOMATICALLY REPAIRS AND RESETS THE DOOR WITHOUT REQUIRING MANUAL REPAIR WORK OR RESETTING OF CONTROLS.
8. FRONT AND REAR SAFETY PHOTOEYES
9. FRONT AND REAR WARNING LIGHTS ACTIVATE WHEN DOOR IS CLOSING.
10. TWO 1/4HP 120V UNHEATED AIR CURTAINS

STANDARD OPTIONS

- ☐ RIGHT HAND MOTOR MOUNT
- ☐ SINGLE SOURCE TRANSFORMER
- ☐ FLOOR MOUNTED SIDE COLUMN GUARD

ACTIVATION

- ☐ — PHOTOEYE
- ☐ — PULL CORDS
- ☐ — MOTION DETECTOR
- ☐ — RADIO CONTROL
- ☐ — PUSHBUTTON
- ☐ — FLOOR LOOP
- ☐ OTHERS (DESCRIBE IN NOTES)

OPTION NOTES

NOTES:
1) 208, 230 & 460V REQUIRES 15 AMP SERVICE.
575V REQUIRES 10 AMP SERVICE.

RYTEC CORPORATION

ONE CEDAR PARKWAY, JACKSON, WI 53037-0403

APPROVAL DRAWING TURBO-SEAL INSULATED - SYSTEM 4

APPROVAL SIGNATURE

FABRICATION CAN PROCEED ACCORDING TO THE SPECIFICATION SHOWN EXCEPT AS NOTED

APPROVED BY:

PRINT NAME: _____

SIGNATURE: _____

DATE: _____

CUSTOMER:

LOCATION:

DATE:

REV.: A

DRAWING NO.: